



**Hard alloy Thread Tap ISO Standard      Coating TiN**

Part.No.	M	P	Z	L1	L2	d2	L5
sg-001	M3	0.5	3	48	11	3.15	7
sg-002	M4	0.7	3	53	13	4	8
sg-003	M4	0.5	3	53	13	4	8
sg-004	M5	0.8	3	58	16	5	9
sg-005	M5	0.5	3	58	16	5	9
sg-006	M6	1	3	66	19	6.3	11
sg-007	M6	0.5	3	66	19	6.3	11
sg-008	M6	0.75	3	66	19	6.3	11
sg-009	M7	1	4	66	19	7.1	11
sg-010	M7	0.75	4	66	19	7.1	11
sg-011	M8	1.25	4	72	22	8	13
sg-012	M8	0.5	4	66	19	8	13
sg-013	M8	0.75	4	66	19	8	13
sg-014	M8	1	4	72	22	8	13
sg-015	M9	1.25	4	72	22	9	14
sg-016	M9	0.75	4	66	19	9	14
sg-017	M9	1	4	72	22	9	14
sg-018	M10	1.5	4	80	24	10	15
sg-019	M10	0.75	4	73	20	10	15
sg-020	M10	1	4	80	24	10	15
sg-021	M10	1.25	4	80	24	10	15

**Note:**

- 1.Right hand thread no mark,"L" noted after specification for left hand thread
- 2.Material: HSS, HSS-E, Hard alloy normally
- 3.TiN or TiALN coating make it have super hardness and longer life.  
also coating according customer's request.
- 4.Standard size normally, customized size available
- 5.When order tell me part no and Q'ty